

0.5m Ka band Automatic Flyaway Antenna

Product Category : Automatic Flyaway



Product Parameters

Antenna Category	Automatic Flyaway
Antenna Aperture	0.5m
Antenna Type	Feed back
Polarization	Circular
Frequency (Rx)	17.70-21.20GHz
Frequency (Tx)	29.00-31.00GHz

Port isolation (Rx-Tx)	$\geq 85 \text{ dB}$
Port isolation (Tx-Rx)	$\geq 40 \text{ dB}$
Gain(Rx)	$\geq 37.88 + 20\lg(f/20.00) \text{ dBi}$
Gain(Tx)	$\geq 41.33 + 20\lg(f/30.00) \text{ dBi}$
VSWR(Rx)	$\leq 1.35:1$
VSWR(Tx)	$\leq 1.35:1$
Motion range (AZ)	$\pm 180^\circ$
Motion range (EL)	$10^\circ \sim 90^\circ$
Motion range (POL)	$\pm 90^\circ$
AZ	$0.1 \sim 3^\circ/\text{s}$
EL	$0.1 \sim 3^\circ/\text{s}$
POL	
Initial acquisition time	$\leq 3 \text{ min}$
Blockage recovery time	$\leq 1 \text{ min}$
Power capacity	$\leq 500 \text{ W}$
Operating Temperature	$-40^\circ\text{C} \sim +60^\circ\text{C}$
Storage Temperature	$-55^\circ\text{C} \sim +70^\circ\text{C}$
Humidity Requirement	95%(20°C)
Operating wind velocity	13m/s
Survival wind velocity	20m/s
Protection grade/IP Rating	IP65
Power supply	90~264VAC,47Hz~63Hz
power consumption	$\leq 350 \text{ W}$ (No power amplifier)
Material	Carbon Fiber
Remarks	

Contact Us

Phone:(86)029-81156153

Email:bxg0@sohu.com

Web:<https://www.nebulasignal.com/>

Address:9th Floor, No. 32 Chuanghui Road, High-tech Zone, Xi'an City, Shaanxi Province, China