

2.4m C band Drive away Satcom Antenna

Product Category : Drive Away



Product Parameters

Antenna Category	Drive Away
Antenna Aperture	2.4m
Antenna Type	Offset
Polarization	Linear
Frequency (Rx)	3.40-4.20GHz
Frequency (Tx)	5.85-6.725GHz
Port isolation (Rx-Tx)	

Port isolation (Tx-Rx)	
Gain(Rx)	$\geq 37.00 + 20\lg(f/3.80)\text{dBi}$
Gain(Tx)	$\geq 41.40 + 20\lg(f/6.30)\text{dBi}$
VSWR(Rx)	$\leq 1.5:1$
VSWR(Tx)	$\leq 1.5:1$
Motion range (AZ)	$\pm 180^\circ$
Motion range (EL)	$10^\circ \sim 90^\circ$
Motion range (POL)	$\pm 90^\circ$
AZ	$0.1 \sim 3^\circ/\text{s}$
EL	$0.1 \sim 1^\circ/\text{s}$
POL	$0.1 \sim 1^\circ/\text{s}$
Initial acquisition time	
Blockage recovery time	
Power capacity	
Operating Temperature	$-40^\circ\text{C} \sim +60^\circ\text{C}$
Storage Temperature	$-55^\circ\text{C} \sim +70^\circ\text{C}$
Humidity Requirement	
Operating wind velocity	
Survival wind velocity	
Protection grade/IP Rating	IP65
Power supply	90~264VAC, 47Hz~63Hz
power consumption	
Material	Carbon Fiber
Remarks	Optional Feed: L / S; 1.00GHz~18.00GHz; 18.00GHz~40.00GHz

Contact Us

Phone:(86)029-81156153

Email:bxg0@sohu.com

Web:<https://www.nebulasignal.com/>

Address:9th Floor, No. 32 Chuanghui Road, High-tech Zone, Xi'an City, Shaanxi Province, China